



Pony Testing International Group

Report No.: 0903133-004~1

# MSDS Report

ACCREDITATION CERTIFICATE OF CHINA NATIONAL  
ACCREDITATION BOARD FOR LABORATORIES (No. CNAS L3192)

Samples

Lithium-ion Power Battery (SE180AHA)

Client Unit

SKY ENERGY (LUOYANG) CO., LTD

Client Address

No.36, High New Tech Development Zone, Luoyang,  
China.

PONY assumes objectivity and fairness of the test, and fulfill the duty of confidentiality for applicant's information. Applicant should undertake responsibility for the authenticity of submitted sample and information. Unless otherwise stated, the results shown in the report refer only to the sample(s) tested. PONY shall not have any economic and legal responsibility because the use of testing result, or direct and indirect losses, and all legal consequences because of the result. This report is invalid without signatures of approver and special seal for inspection of PONY, or it has been reproduced in full or part. This Report is issued by PONY subject to its General Conditions of Service. Any unauthorized alteration, forgery or falsification of the content is unlawful, offenders may be prosecuted to the fullest extent of the law.



Pony Testing International Group

[www.ponytest.com](http://www.ponytest.com)

Hotline 400-819-5688

Add: Yingzhi Building, No. 49-3, Suzhou Road, Haidian District, Beijing

Tel: (010) 82618116

Fax: (010) 82619629

E-mail: [pony@ponytest.com](mailto:pony@ponytest.com)

Building 35, No. 680, Guiping Road, Xuhui District, Shanghai

(021) 64851999

(021) 64856403

[csh@ponytest.com](mailto:csh@ponytest.com)

Building 6 of Zhongxing Industry City, Chuangye Road, Nanshan District, Shenzhen

(0755) 26050909

(0755) 26068336

[sz@ponytest.com](mailto:sz@ponytest.com)





Pony Testing International Group

## Material Safety Data Sheet

### Section 1 - Chemical Product and Company Identification

**Product Name:** Lithium-ion Power Battery (SE180AHA)

**Sample Code:** SE180AHA

**Manufacture:** SKY ENERGY (LUOYANG) CO., LTD

**Address:** No.36, High New Tech Development Zone, Luoyang, China.

**Post Code:** 471003

**Tel:** 0379-65106062

**Emergency Telephone:** 0379-65106062

**Fax:** 0379-65106088

**Email:** TK@skyenergy.com.cn

### Section 2 - Composition/Information on Ingredient

Chemical Name	CAS No.	In % By Weight
Fe	7439-89-6	42
P	7723-14-0	16
Mn	7439-96-5	0.5
Ca	7440-70-2	0.3
Graphite	7782-42-5	5
Na	7440-23-5	0.01
C	7440-44-0	3.1
Li	7439-93-2	3.4
PE	9002-86-2	3.3
Cu	7440-50-8	10
Al	7429-90-5	6
Lix	---	8
F	7782-41-4	3.3

www.ponytest.com Hotline 400-819-5688

Add: Yingzhi Building, No.49-3, Suzhou Road, Haidian District, Beijing	Building 35, No.680, Guiping Road, Xuhui District, Shanghai	Building 6 of Zhongxing Industry City, Chuangye Road, Nanshan District, Shenzhen
Tel: (010)82618116	(021)64851999	(0755)26050909
Fax: (010)82619629	(021)64856403	(0755)26068336
E-mail: pony@ponytest.com	csh@ponytest.com	sz@ponytest.com





Pony Testing International Group

### Section 3 - Hazards Identification

#### Routes of Entry

Inhalation, Skin, Ingestion.

#### Health Hazards (Acute and Chronic)

These chemicals are contained in a sealed can. Risk of exposure occurs only if the battery is mechanically or electrically abused. The most likely risk is acute exposure when a battery vents.

#### Sign/Symptoms of Exposure

May be a reproductive hazard. Lithium can cause thermal and chemical burns upon contact with the skin.

#### Medical Conditions Generally Aggravated by Exposure

An acute exposure will not generally aggravate any medical condition.

### Section 4 - First Aid Measures

#### Eyes

Flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical aid.

#### Skin

Remove contaminated clothes and rinse skin with plenty of water or shower for 15 minutes. Get medical aid.

#### Inhalation

Remove from exposure and move to fresh air immediately. Use oxygen if available.

#### Ingestion

Give at least 2 glasses of milk or water. Induce vomiting unless patient is unconscious. Call a physician.

### Section 5 - Fire Fighting Measures

**Flash Point:** N/A.

**Auto-Ignition Temperature:** N/A.

#### Extinguishing Media

Water.

#### Firefighting

In case of fire in an adjacent area, use water, CO<sub>2</sub> or dry chemical extinguishers

www.ponytest.com Hotline 400-819-5688

Add: Yingzhi Building, No. 49-3, Suzhou Road, Haidian District, Beijing

Tel: (010) 82618116

Fax: (010) 82619629

E-mail: pony@ponytest.com

Building 35, No. 680, Guiping Road, Xuhui District, Shanghai

(021) 64851999

(021) 64856403

csb@ponytest.com

Building 6 of Zhongxing Industry City, Chuangye Road, Nanshan District, Shenzhen

(0755) 26050909

(0755) 26068336

sz@ponytest.com





Pony Testing International Group

if batteries in their original containers since the fuel of the fire is basically paper products. For bulk quantities of unpackaged batteries use appropriate method. In this case, do not use water.

## Section 6 - Accidental Release Measures

### Steps to be Taken in case Material is Released or Spilled

If the battery is accidentally broken and organic electrolyte leaks out, wipe it up with a cloth, and dispose of it in a plastic bag and put into a steel can.

The preferred response is to leave the area and allow the batteries to cool and vapors to dissipate. Provide maximum ventilation. Avoid skin and eye contact or inhalation of vapors. Remove spilled liquid with absorbent and incinerate.

### Waste Disposal Method

It is recommended to discharge the battery to the end, handing in the abandoned batteries to related department unified, dispose of the batteries in accordance with approved local, state, and federal requirements. Consult state environmental protection agency and/or federal EPA.

## Section 7 - Handling and Storage

The batteries should not be opened, destroyed or incinerate, since they may leak or rupture and release to the environment the ingredients that they contain in the hermetically sealed container.

Do not short circuit terminals, or over charge the battery, forced over-discharge, throw to fire. Do not crush or puncture the battery, or immerse in liquids.

### Precautions to be taken in handling and storing

Avoid mechanical or electrical abuse. Storage preferably in cool, dry and ventilated area, which is subject to little temperature change. Storage at high temperatures should be avoided.

Do not place the battery near heating equipment, nor expose to direct sunlight for long periods.

### Other Precautions

Batteries may explode or cause burns, if disassembled, crushed or exposed to fire or high temperatures. Do not short or install with incorrect polarity.

## Section 8 - Exposure Controls, Personal Protection

### Respiratory Protection

www.ponytest.com Hotline 400-819-5688

Add: Yingzhi Building, No.49-3, Suzhou Road, Haidian District, Beijing	Building 35, No.680, Guiping Road, Xuhui District, Shanghai	Building 6 of Zhongxing Industry City, Chuangye Road, Nanshan District, Shenzhen
Tel: (010)82618116	(021)64851999	(0755)26050909
Fax: (010)82619629	(021)64856403	(0755)26068336
E-mail: pony@ponytest.com	csh@ponytest.com	sz@ponytest.com





Pony Testing International Group

In case of battery venting, provide as much ventilation as possible. Avoid confined areas with venting batteries. Respiratory Protection is not necessary under conditions of normal use.

**Ventilation**

Not necessary under conditions of normal use.

**Protective Gloves**

Not necessary under conditions of normal use.

**Other Protective Clothing or Equipment**

Not necessary under conditions of normal use.

**Personal Protection is recommended for venting batteries**

Respiratory Protection, Protective Gloves, Protective Clothing and safety glass with side shields.

Section 9 - Physical and Chemical Properties

**Nominal Voltage:** 3.2V.

**Rated Capacity:** 180AH.

**Appearance Characters:** Blue, odorless, quadrate battery.

Section 10 - Stability and Reactivity

**Stability**

Stable

**Conditions to Avoid**

Heating, mechanical abuse and electrical abuse.

**Hazardous Decomposition Products**

N/A.

**Hazardous Polymerization**

N/A.

If leaked, forbidden to contact with strong oxidizers, mineral acids, strong alkalies, halogenated hydrocarbons.

Section 11 - Toxicological Information

Inhalation, skin contact and eye contact are possible when the battery is opened. Exposure to internal contents, the corrosive fumes will be very irritating

www.ponytest.com Hotline 400-819-5688

Add: Yingzhi Building, No. 49-3, Suzhou Road, Haidian District, Beijing	Building 35, No. 680, Guiping Road, Xuhui District, Shanghai	Building 6 of Zhongxing Industry City, Chuangye Road, Nanshan District, Shenzhen
Tel: (010) 82618116	(021) 64851999	(0755) 26050909
Fax: (010) 82619629	(021) 64856403	(0755) 26068336
E-mail: pony@ponytest.com	esh@ponytest.com	sz@ponytest.com





Pony Testing International Group

to skin, eyes and mucous membranes. Overexposure can cause symptoms of non-fibrotic lung injury and membrane irritation.

## Section 12 - Ecological Information

When promptly used or disposed the battery does not present environmental hazard. When disposed, keep away from water, rain and snow.

## Section 13 - Disposal Considerations

### APPROPRIATE METHOD OF DISPOSAL OF SUBSTANCE OR PREPARATION

If batteries are still fully charged or only partially discharged, they can be considered a reactive hazardous waste because of significant amount of unreacted, or unconsumed lithium remaining in the spent battery. The batteries must be neutralized through an approved secondary treatment facility prior to disposal as a hazardous waste. Recycling of battery can be done in authorized facility, through licensed waste carrier.

## Section 14 - Transport Information

This Lithium-ion Power Battery (SE180AHA) have passed UN38.3 test and according to the report No. 0903133-005 and 0903133-005a. It belongs to the 9th dangerous goods. According to NEW PACKING INSTRUCTION 965 ~ 970 of IATA DGR 50<sup>th</sup> Edition for transportation.

### Air transport ICAO-TI and IATA-DGR:

**IATA Proper Shipping Name:** Lithium ion batteries + (including lithium polymer batteries)

**Hazard Class:** 9

**Identification Number:** UN3480

**Packaging group:** II

**Maritime Transport IMDG:** Lithium ion batteries + (including lithium polymer batteries)

**IMDG Class:** 9

**UN Number:** UN3480

www.ponytest.com  Hotline 400-819-5688

Add: Yingzhi Building, No.49-3, Suzhou Road, Haidian District, Beijing

Tel: (010)82618116

Fax: (010)82619629

E-mail: pony@ponytest.com

Building 35, No. 680, Guiping Road, Xuhui District, Shanghai

(021)64851999

(021)64856403

csb@ponytest.com

Building 6 of Zhongxing Industry City, Chuangye Road, Nanshan District, Shenzhen

(0755)26050909

(0755)26068336

sz@ponytest.com





Pony Testing International Group

More information concerning shipping, testing, marking and packaging can be obtained from Label master at <http://www.labelmaster.com>.

Separate Li-ion batteries when shipping to prevent short-circuiting. They should be packed in strong packaging for support during transport.

In the case of transportation, confirm no leakage and no overspill from a container. Take in a cargo of them without falling, dropping and breakage. Prevent collapse of cargo piles and wet by rain. The container must be handled carefully. Do not give shocks that result in a mark of hitting on a cell. Please refer to Section 7-HANDLING AND STORAGE also.

**Transport Fashion:** By air, by sea.

## Section 15 - Regulatory Information

### Law Information

《Dangerous Goods Regulation》  
 《Recommendations on the Transport of Dangerous Goods Model Regulations》  
 《International Maritime Dangerous Goods》  
 《Classification and code of dangerous goods》  
 OSHA Hazard Communication Standard Status  
 Toxic Substances Control Act (TSCA) Status  
 SARA Title III  
 RCRA  
 In accordance with all Federal, State and Local laws.

## Section 16 - Additional Information

The above information is based on the data of which we are aware and is believed to be correct as of the data hereof. Since this information may be applied under conditions beyond our control and with which may be unfamiliar and since data made available subsequent to the data hereof may suggest modifications of the information, we do not assume any responsibility for the results of its use. This information is furnished upon condition that the person receiving it shall make his own determination of the suitability of the material for his particular purpose.

MSDS Creation Date: March 17, 2009